Safety Data Sheet

Santian 1	l Chamiaal	Draduct of	nd Campany	Identification

Product Name Viscosity Grades Company Name: Date:

Syn Gear SGO 600 Series Fully Synthetic Industrial Gear and Bearing Oil

630

Reliant Technologies, Inc. 2933 Hwy 1 North Port Allen, Louisiana 70767

Revised 5/12/2015

Emergency Phone:	Product Code		
225-383-7923	1-7630		

Section 2 - Hazards Identification

HMIS CODE INFORMATION:	Health	Flammability	Reactivity	Personal Protection (PPE)
NFPA HAZARD ID	0	1	0	
HMIS HAZARD ID	0	1	0	В

GHS CLASSIFICATION This material is not hazardous according to regulatory guidelines (see SDS Section 15)

GHS LABEL ELEMENTS Symbol(s): None Signal Word: None Hazard Statements: None

HAZARD NOT OTHERWISE CLASSIFIED (HNOC): None as defined under 29CFR1910.1200 PHYSICAL / CHEMICAL HAZARDS: No significant hazards.

HEALTH HAZARDS: High pressure injection under skin may cause serious damage. Excessive exposure may result in eye, skin,

or respiratory damage.

ENVIRONMENTAL HAZARDS: No significant hazards.

This material should never be used for any other purpose than the intended use in Section 1. Health studies have shown that chemical exposure may cause potential human health risks wich may vary from person to person.

Section 3 - Composition and Information on Ingredients

This material is defined as a mixture.

Composition	CAS#	% by Weight	GHS Codes
Synthetic Hydrocarbons	64742-54-7	<100%	H315, H318
Additive Mixture	Confidential	< 30%	H315, H318, H401, H411

As per paragraph (i) of 29CFR1910.1200, this formulation is considered a trade secret and spedific chemical identity and exact ccomposition percentages may be withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, emergency employees, or their designated representatives accordance with the provisions of paragraph (i).

Section 4 - First Aid Measures

FIRST AID

INHALATION: Remove from further exposure. First responders should avoid exposure while providing assistance. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconscionsness occurs, seek immediate medical attention. If breathing has stopped, provide artificial respiration until emergency personnel arrive

CONTACT: Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physicial as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment, within the first few hours, may significantly reduce the untimate extent of the injury.

EYE CONTACT: Flush with copius amounts of water for at least 15 minutes. Seek immediate medical attention

INGESTION: First aid is not normally required unless large amounts are ingested.

Seek medical attention if irritation or discomfort occurs.

Section 5 - Fire Fighting Measures

FLASH POINT: > 300 F METHOD: ASTM D-92

FLAMABLE LIMITS (APPROXIMATE VOLUME % IN AIR): LEL N/D UEL N/D

FIRE EXTINGUISHING MEDIA: Water fog, foam, dry chemical or CO2

FIRE FIGHTING INSTRUCTIONS: Evacuate area and prevent fire control runoff from entering streams or storm drains.

Firefighters should use standard PPE in enclosed places, including self-contained breathing

apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

HAZARDOUS COMBUSTION PRODUCTS: Aldehydes, sufur oxides, incomplete combustion products, oxides of carbon, smoke

Svn Gear SGO 630 Page 2/4 Revised 5/12/2015

Section 6 - Accidental Release Measures

NOTIFICATION PROCEDURES: In the event of a spill or accidental release, notify appropriate authorities in accordance

with all local, state, and federal regulations. Releases of oil are required to be reported when they exceed the applicable reportable quantity, or when they could reach any waterw including intermittent dry creeks. The National Response Center number is (800) 424-8802

PROTECTIVE MEASURES: Avoid contact with spilled material. Comnsult appropriate section of this SAFETY DATA

SHEET. Additional protective measures may be necessary depending on the specific circumstances and/or the judgment of the emergency responders present on the scene.

SPILL MANAGEMENT: ON LAND: Stop leak if this can be done without risk. Recover spill using pump, vacuum, or absorbant

> ON WATER: Stop leak if this can be done without risk. Confine the spill with containment booms

Warn shipping, Remove from water surface by skimming or with absorbants. Obtain

regulatory permission prior to considering the use of dispersants.

ADDITIONAL SPILL CONSIDERATIONS: The above recommendations are based on the most likely spill scenario, but geographic

conditions, weather, and water conditions (wave, currents, etc) may affect the decision as to the most appropriate action to be taken. In addition, regulations may prescribe or limit the actions that may be taken. For this reason, expert spill response personnel should be

ENVIRONMENTAL PRECAUTIONS: For large spills, dike far ahead of liquid apill for later recovery and disposal.

Prevent entry into waterways buildings, and confined areas.

Section 7 - Handling and Storage

HANDLING:

Avoid contact with used product. Prevent small spill and leaks to avoid a slip hazard. Product can accumulate static charges which may cause an electrical spark that can act as an ignition source. When the product is handled in bulk, an electrical spark couild ignite any flammable vapors from liquids or residues that may be present (such as fuels). Use proper grounding procedures. Consult API paper "Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents" or NFPA 77 (Recommended Practice on Static Electricity"

This material is a Static Accumulator

STORAGE: The type of container or storage vessel may effect the static accumulation and dissipation. Do not store in open or unlabeled containers. Keep away from oxidizers and other incompatible materials.

Section 8 - Exposure Controls / Personal Protection

EXPOSURE LIMITS / STANDARDS FOR When mists or aerosols can occur, the following exposure limits are reccommended:

MATERIALS THAT CAN BE FORMED ACGIH TLV 5 mg/m3 (Inhalable Fraction)

WHEN HANDLING THIS PRODUCT: OSHA PEL 5 mg/m3

> NOTES: LIMITS / STANDARDS SHOWN ARE FOR GUIDANCE ONLY. NO BIOLOGICAL LIMITS HAVE BEEN DETERMINED

ENGINEERING CONTROLS: The levels of protection and types of controls necessary will vary, depending upon

the conditions surround the use of the product.

CONTROL MEASURES TO CONSIDER: No special requirements under ordinary use conditions, and provided there is adequate

Personal protective equipment (PPE) selections vary based on potential exposure conditions, such as applications, handling practices, concentration, and ventilation. Information on the PERSONAL PROTECTION:

selection of PPE for use with this product, as provided below, is based upon intended,

normal usage.

RESPIRATORY PROTECTION: If engineering controls do not maintain airborne contaminant concentrations at a level which

is adequate to protect worker health, an approved respirator may be needed. Respirator selection, use, and maintainance must be in accordance with all regulatory requirements, such as OSHA, MSHA, etc. There are no special respirator requirements under normal conditions

of use, and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning devices are not in use, or if air purifying filter capacity/rating may be exceeded.

SKIN PROTECTION: No specific protection is ordinarily required under normal conditions of use. If gloves are used, glove suitability will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection for your use conditions. Inspect

and replace worn or damaged gloves.

No special protective clothing is ordinarily required under normal conditions of use. In

accordance with good industrial hygene, precautions should be taken to avoid skin contact.

EYE PROTECTION: Safety glasses with side shields. Maintain nearby eve wash stations in all work area

SPECIFIC HYGENE MEASURES: Observe good personal hygiene. Wash after handling product and before eating, drinking, or smoking. Wash work clothes and PPE to remove contaminants. Discard clothes and shoes/

boots that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTALS CONTROLS: Comply with all local, state and federal regulations limiting discharges to air, water, and

soil. Apply appropriate control measures to prevent or limit any potential emissions.

Svn Gear SGO 630 Page 3/4 Revised 5/12/2015

Section 9 - Physical and Chemical Properties

NOTE: Physical and chemical properties are provided for safety, health, and environmental considerations only,

and may not fully represent product specifications.

PHYSICAL FORM Liquid N/A pH BOILING POINT COLOR Ambe

> 600 F > 300 F FLASH POINT
FLAMMABLE LIMITS. % in air ODOR Typical lubricant odor ASTM D-92 Not applicable LEL: N/D UEL: N/D SPECIFIC GRAVITY VAPOR DENSITY, air = 1 < 1 at STP conditions N/D

Negligible SOLUBILITY IN WATER EVAPORATION RATE

Section 10 - Stability and Reactivity

REACTIVITY: Will combust, can be oxidized

STABILITY: Stable under normal conditions of storage and use CONDITIONS TO AVOID: MATERIALS TO AVOID: Excesssive heat and all sources of ignition

Strong oxidizers HAZARDOUS DECOMPOSITION PRODUCTS: HAZARDOUS POLYMERIZATION: Will not occur

Section 11 - Toxicological Information

INHALATION ACUTE TOXICITY Minimally toxic based on an assessement of the components

Negligible hazard at normal, ambient handling temperatures.

Not expected to cause cancer

ACUTE TOXICITY INGESTION Minimally toxic based on an assessement of the components

SKIN ACUTE TOXICITY Minimally toxic based on an assessement of the components

IRRITATION / CORROSION Negliglible irritation to skin at ambient temperatures.

EYE SERIOUS DAMAGE / IRRITATION May cause mild, short-term discomfort to eyes.

Not expexted to be a respiratory sensitizer Not expexted to be a skin sensitizer SENSITIZATION RESPIRATORY TRACT

ASPIRATION RESPIRATORY TRACT Not expected to be an aspiration hazard

Not expected to be a germ cell mutagen. GERM CELL MUTAGENICITY

REPORDUCTIVE TOXICITY Not expected to be a reproductive toxicant

LACTATION Not expected to cause harm to breast-fed children

SPECIFIC TARGET SINGLE EXPOSURE

Not expected to cause organ damage from a single exposure Not expected to cause organ damage from prolongued or repeated exposure ORGAN TOXICITY REPEATED EXPOSURE

OTHER INFORMATION Use good industrial hygene practices

CONTAINS High purity synthetic base oils

Section 12 - Ecological Information

CARCINOGENICITY

ECOTOXICITY Not expexted to be harmful to aquatic organisms

MOBILITY BASE OIL COMPONENT: Low solubility; floats on water and is expected to migrate from water to the land

Expected to partition to sediment and wastewater solids

Section 13 - Disposal Considerations

DISPOSAL RECOMMENDATIONS ARE BASED ON UNUSED MATERIAL. DISPOSAL MUST BE IN ACCORDANCE WITH ALL LOCAL STATE AND FEDERAL REGULATIONS AND MUST BE BASED ON THE MATERIAL CHARACTERISTICS AT THE TIME OF DISPOSAL.

DISPOSAL RECOMMENDATIONS: Product is suitale for burning in an enclosed, controlled burner for fuel value or for disposal

by supervised inceneration at very high temperatures to prevent the formation of undesirable combustion products. Dispose of used oil at designated sites. Minimize skin contact. Do not mix used oils with solvents, brake fluid, or coolants.

REGULATORY INFORMATION: RCRA Information: The unused product is not listed by the EPA as a hazardous waste

(40 CFR, Part 261D), nor does it exhibit any hazardous waste characteristics.

This product is not formulated with any contaminant as determined by the Toxic Characteristic Leaching Procedure (TCLP).

EMPTY CONTAINER WARNING: Empty containers may contain residue and can be dangerous. Do not attempt to clean or

refill an empty container. Empty drums should be sent for recycling or disposal in accordance with all governmental regulations.

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, OR GRIND ON EMPTY CONTAINERS, OR EXPOSE THEM TO HEAT, SPARKS, A STATIC DISCHARGE, OR ANY OTHER SOURSE OF IGNITION. THIS COULD RESULT IN AN EXPLOSION CAUSING INJURY OR DEATH.

Svn Gear SGO 630 Page 4/4 Revised 5/12/2015

Section 14 - Transportation Information

LAND - US DEPARTMENT OF TRANSPORTATION LAND - CANADA TRANSPORTATION OF DANGEROUS GOODS

SEA (INTERNATIONAL MARINE DANGEROUS GOODS

AIR - INTERNATIONAL AIR TRANSPORT ASSOCIATION

EPCRA SECTION 302 STATUS SARA 311/312 REPORTABLE HAZARD CATAGEORIES

Not Regulated for Land Transport Not Regulated for Sea Transport MARINE POLLUTANT

Not Regulated for Air Transport

Not Regulated for Land Transport

Section 15 - Regulatory Information OSHA HAZARD COMMUNICATION STANDARD:

Not considered hazardous per OSHA HazCom 2012, 29 CFR 1910,1200

All components listed, or are exempt

All components listed, or are exempt

This material contains no extremely hazardous substances

No components subject to requirements of SARA 313 Toxic Release Program

Section 16 - Other Information

SARA 313 TOXIC RELEASE INVENTORY

TSCA STATUS
CANADIAN DSL STATUS

ABBREVIATIONS Denotes the section in question "does not apply" to this product

STP Standard temperature and Pressure

CAS# Chemical Abstract Service number

ACGIH American Conference of Governmental Industrial Hygienists

National Institute for Occupational Safety and Health Threshold Limit Value NIOSH TLV

PEL Permissible Exposure Limit STEL **Short Term Exposure Limit**

National Toxicology Program
International Agency for Research on Cancer NTP IARC

Biochemical Oxygen Demand

KEY TO "H" CODES CONTAINED IN SECTION 3: H315 Can cause skin irritation

Can cause serious eye damage H318

H401 Toxic to aquatic life

Toxic to aquatic life with long lasting effects

THIS SAFETY DATA SHEET IS MADE IN ACCORDANCE WITH GLOBAL HARMONIZATION SYSTME REQUIREMENTS

Disclaimer:

This safety information is provided to assist customers in assessing measures necessary for compliance with health, safety, and environmental regulations. Individuals handling this product should be informed of the recommended safety precautions, and should have access to this information. The information contained herein is based on available data, and is believed to be accurate. No guarantee or warranty is provided, since the use of this product is within the exclusive control of the user, and it is the user's responsibility to satisfy itself that this information is suitable and complete for its particular use. Customers are responsible for compliance with local, state, and federal regulations that may be pertinent in the storage, application, and disposal of this product.