

Industrial Blue

Extra Heavy Duty Cleaner and
Degreaser



POWERFUL | EFFICIENT | ENVIRONMENTALLY SAFE

Industrial blue is an all purpose, water soluble cleaner that has proven itself outstanding in a variety of cleaning operations. It is completely soluble in fresh or salt water. Industrial blue is convenient, and can be used on painted surfaces without fear of damage. It can be used with cold or hot water, or with spray, steam, and pressure equipment.



Industrial blue is highly concentrated, and it will perform most cleaning tasks with a minimum amount of material, unlike many “pre-diluted” or “ready to use” cleaning products. This reduces both cleaning time and cost. In addition, and most importantly, Industrial Blue generates significantly less waste water to be treated prior to discharge. Industrial blue is safe.

Industrial Blue contains no caustic soda, caustic potash, or ammonia, and has no SARA Title III, Section 313 listed ingredients, nor any known or suspected carcinogenic or toxic substance.

Industrial Blue is offered in 275 gallon tote tanks, or 55 gallon drums.



RELIANT TECHNOLOGIES

local | quality | service

2933 HWY 1 North
Port Allen, LA 70767

Phone: 225 383 7923 | Fax: 225 383 7961
ReliantLubrication.com

Reliant Technologies
Across the South and Around the World...

Industrial Blue

PHYSICAL PROPERTIES

Product	Industrial Blue
Color	Blue
Density	8.4/bs/gal
Freezing Point	<25°F
pH	12.8-12.9
Flash Point	None by any method
Biodegradability	Complete
Phosphorous Content	None
Free Alkali Content	None
Sara Title 313	None

USES

All cleaning jobs will be made easier when Industrial Blue is used in accordance with these simple directions.

CARPET STAIN REMOVER: To remove carpet stains spray on full strength.

WAX STRIPPING: To remove floor wax stripping polishes use full strength.

EXTERIOR OF BUILDINGS (CERAMIC & PORCELAIN) : Use in 50% dilution with water.

TERRAZZO & MARBLE FLOORS & WALLS: Use on terrazzo & marble floors & walls 2 cups per 3 gallons of warm water.

ASPHALT TILE & LINOLEUM FLOORS: Use on asphalt tile & linoleum floors 2 cups per 3 gallons of warm water.

VINYL & RUBBER FLOORS: Use 2 cups vinyl & rubber floors per 3 gallons of warm water.

ALUMINUM, STAINLESS STEEL, ENAMELED CABINETS, FILES, & LOCKERS: Use full strength.

WINDOW CLEANING: Use 2.5 cups per gallon of water.

GENERAL DEGREASING: Use full strength.

FOOD PROCESSING PLANTS, BAKERIES, DAIRIES, CANNERIES: Use various dilutions depending on conditions.

KITCHENS, OVENS, CANOPIES, HOODS, GRILLS, DUCTS: Use full strength.

REFRIGERATORS & DEEP FREEZERS: Use full strength.

2933 HWY 1 North
Port Allen, LA 70767

Phone: 225 383 7923
Fax: 225 383 7961
ReliantLubrication.com