

Syn-Dyne 320

Premium Automatic Transmission Fluid



HEAT TRANSFER | PREVENTS CORROSION | HIGH VI

Syn-Dyne 320 Premium Automatic Transmission Fluid provides excellent oxidation and friction stability, anti wear properties, and low temperature fluidity desired for most automatic transmissions, has improved friction durability and stability, and has better shifting performance, and wear protection.



PERFORMANCE PROPERTIES

- Good Heat Transfer
- Superior Oxidation Stabilization
- Corrosion Prevention
- Elastomer Compatibility
- High Viscosity Index
- Inhibits Against Foaming
- Excellent Lubricating Characteristics

Syn-Dyne 320 is offered in 275 gallon tote tanks, 55 gallon drums, or 5 gallon pails.

MEETS OR EXCEEDS THE FOLLOWING:

- GM Dextron III
- Allison C-4
- Ford Mercon
- Caterpillar T-02

CONFORMS WITH THE FOLLOWING MANUFACTURER'S REQUIREMENTS:

- Voith
- Denison Hydraulics
- Sperry Vulers
- Sundstrand Hydraulics



RELIANT TECHNOLOGIES

local | quality | service

2933 HWY 1 North
Port Allen, LA 70767

Phone: 225 383 7923 | Fax: 225 383 7961
ReliantLubrication.com

Reliant Technologies
Across the South and Around the World...

Syn-Dyne 320

Syn-Dyne 320 Premium Automatic Transmission Fluid also has lubricity characteristics for quiet operation. Syn-Dyne 320 Premium Automatic Transmission Fluid will resist break down from the heat and loss of lubricity, and has more oxidation stable than other transmission fluids.

PHYSICAL PROPERTIES

Attribute	Value
Gravity, API	37.8
Viscosity (cSt) @ 100° C	7.4
Viscosity (cSt) @ 40° C	32.4
Viscosity Index	197.5
Flash Point, F°	450
Specific Gravity @ 60° F	0.8358
Pounds Per Gallon	9.96

Syn-Dyne 320 Premium Automatic Transmission Fluid is a high performance, long life, multi-purpose automatic transmission fluid. Syn-Dyne 320 Premium Automatic Transmission Fluid is formulated with very high viscosity index base oils, and is fully compatible with, and can be mixed with other automatic transmission fluids. For best results, however, drain oil, then re-fill with Syn-Dyne 320 Premium Automatic Transmission Fluid.

2933 HWY 1 North
Port Allen, LA 70767

Phone: 225 383 7923
Fax: 225 383 7961
ReliantLubrication.com