

Syn-Ultra

Fully Synthetic Extra Heavy Duty
Industrial Engine Oil



FUEL EFFICIENT | REDUCED EMISSIONS | HIGH VI

Syn-Ultra is a high performance, fuel-efficient motor oil for universal application in both gasoline and diesel engines. Syn-Ultra is made from synthetic base stocks that are thermally stable, resist oxidation, fight corrosion and extend drain intervals.



PERFORMANCE PROPERTIES

- Increase Engine Cleanliness
- Substantial Reduction in Cylinder Wear
- Reduces Bearing Wear and Piston Deposits
- Excellent Valve Train Protection
- Reduces Oil Consumption
- Effective Cold Cranking Technology

Syn-Ultra Fully Synthetic Extra Heavy Duty Industrial Engine Oils are environmentally friendly, and are formulated to insure toxic emissions are minimized. Syn-Ultra is offered in 275 gallon tote tanks, 55 gallon drums, or case gallons.

MEETS OR EXCEEDS THE FOLLOWING:

- API CJ-4
- API SM
- All Previous API Categories
- Cummins CE S 20081
- Mack E0-O Premium Plus
- Detroit Diesel DDC 93K218
- CAT ECF-3
- CAT ECF-2
- CAT ECF-1-a
- ACEA E9-08 (2008)
- ACEA E7-04 issue 2 (2007)
- MB-Approval 226.31
- MAN 3575
- MAN 3275
- MTU Type 2.1
- Volvo VDS-4
- Volvo VDS-3
- Renault Truck RLD-3
- Deutz DQC III-05



RELIANT TECHNOLOGIES

local | quality | service

2933 HWY 1 North
Port Allen, LA 70767

Phone: 225 383 7923 | Fax: 225 383 7961
ReliantLubrication.com

Reliant Technologies
 Across the South and Around the World...

Syn-Ultra

Technology driven additive packages, based on proprietary chemistry are designed to shield engines from wear, rust, oxidation, and corrosion, while keeping internal surfaces clean. Syn-Ultra provides exceptional engine performance at elevated temperatures, helping to improve fuel efficiency and extend engine life.

PERFORMANCE PROPERTIES

SAE Grade	15w-40
API Gravity @ 60° F	30.4
LBS/GAL	7.29
Specific Gravity @ 60° F	0.8741
Viscosity @ 100° C	15.0
Viscosity @ 40° C	91
Viscosity Index	175
Flash Point (Open Cup)	490
Pour Point, F	-39
Base Number	9.0
CCS cP (°C)	6450@-20C
MRV TP-1 cP (°C)	14,600@-25
Sim-D % off @ 700° F	6.41
Noack % off @ 250° C	11.9
Sulfated Ash	.09
Phosphorus, wt%	0.106

2933 HWY 1 North
 Port Allen, LA 70767

Phone: 225 383 7923
 Fax: 225 383 7961
ReliantLubrication.com